



### Experience powerful performance in a compact design.

The EcoTank L4360 offer high-quality, ultra-low-cost printing with an 8,500<sup>\*1</sup> ultra-high page yield ink bottle. Thanks to Heat-Free Technology, users can also print responsibly with lower power consumption.









Print Speed (Black)

Ultra-High Page Yield (Black)

Duplex Printing

Replaceable Maintenance Box









Wi-Fi Direct

Epson Connect®

Ensor Smart Panel (Mobile Print)

Warranty'5











## **Improved Design**

The all-new EcoTank printer is more compact and lighter, making it an ideal fit for any home or small office environment.

## **Productivity Meets Durability**

Enjoy fast printing with auto-duplex functionality at speeds of up to 15 ipm<sup>2</sup>. Designed with durability in mind, you can print up to 50,000 pages covered under warranty\*5.

# **Ultra Low Printing Cost**

Print with confidence using our high-yield, low-cost ink bottles. Our pigment-based black ink ensures water-resistant prints for black-and-white documents.

Applicable to 001 BK ink bottle only.

Print speed is based on simplex black-and-white printing, measured in accordance with ISO 24734 on A4-sized paper. Supported Epson Connect features: Epson Smart Panel, Epson Email Print and Remote Print Driver.

Epson Smart Panel App from IOS or Android App Stores.

<sup>15 1</sup> year or 50,000 pages whichever comes earlier, print head included under warranty.

### **SPECIFICATIONS**

Model Number	L4360		
Printer Type	Print, Scan, Copy		
Printing	Trink, Coarl, Copy		
Printing Technology	PrecisionCore Printhead		
lozzle Configuration	400 x 1 nozzles Black		
ŭ	128 x 1 nozzles per colour (Cyan, Magenta, Yellow)		
Print Direction	Bi-directional printing		
Maximum Resolution	4,800 x 1,200 dpi (with Variable-Sized Droplet Technology)		
Vinimum Ink Droplet Volume	3.3 pl		
Print Speed <sup>1</sup>	· ·		
Draft Text - Memo, A4 (Black#1 / Colour#2)	Up to 33 ppm / 20 ppm		
ISO 24734, A4 (Black / Colour)	Simplex: Up to 15.0 ipm / 8.0 ipm   Duplex: Up to 6.5 ipm / 4.5 ipm		
First Page Out Time (Black / Colour)	Simplex: Approx. 9.0 sec / 15.0 sec   Duplex: Approx. 17.0 sec / 25.0 sec		
Photo Default - 10 x 15 cm / 4 x 6""2 #3	Approx. 60 sec / 82 sec		
(Border / Borderless)			
Printer Language	ESC/P-R		
automatic 2-sided printing	Yes Yes		
Copying			
Copy Speed			
ISO 29183, A4 (Black / Colour), Flatbed	Up to 11 ipm / 5.5 ipm		
Copy Quality	Standard / High		
Reduction / Enlargement	25 – 400%		
Naximum Copies from Standalone	99 copies		
Maximum Copy Resolution	600 x 600 dpi		
Maximum Copy Size	A4, LTR		
Scanning			
Scanner Type	Flatbed colour image scanner		
Sensor Type	CIS		
Optical Resolution	1,200 x 2,400 dpi		
Naximum Scan Area	216 x 297 mm (8.5 x 11.7")		
Scanner Bit Depth			
Colour	48-bit input, 24-bit output		
Grayscale	16-bit input, 8-bit output		
Black & White	16-bit input, 1-bit output		
Scan Speed (Flatbed)			
Monochrome 200 dpi	Up to 10 sec		
Colour 200 dpi	Up to 24 sec		
Paper Handling			
Paper Feed Method	Friction feed		
Number of Paper Trays	1		
Paper Hold Capacity			
Input Capacity	100 sheets of A4 Plain Paper (80g/m²)		
	20 sheets of Premium Glossy Photo Paper		
Output Capacity	30 sheets of A4 Plain Paper (80g/m²)		
	20 sheets of Premium Glossy Photo Paper		
Support Paper Size	A4, A5, A6, B5, B6, Letter, Legal, Indian-Legal, 100 x	148mm, 3.5 x 5", 4 x 6", 5 x 7", 5 x 8",	
	8 x 10", 8.5 x 13", 16:9 Wide, 16K, Envelopes: #10, D	DL, C6	
Maximum Paper Size	215.9 x 1,200 mm (8.5 x 47.24")		
Print Margin	0 mm top, left, right, bottom via custom settings in prin	nter driver <sup>*3</sup>	
Support Paper Weight			
Plain Paper	64 – 90 g/m²		
Photo Paper	102 – 300 g/m²		
nterface			
JSB	USB 2.0		
Vetwork	Wi-Fi IEEE 802.11b/g/n, Wi-Fi Direct		
Network Protocol	TCP/IPv4, TCP/IPv6		
Network Printing Protocol	LPD, PORT9100, WSD		
letwork Management Protocols	SNMP, HTTP, DHCP, APIPA, PING, DDNS, mDNS, SLP, WSD, LLTD		
Control Panel			
.CD Screen	3.7 cm (1.44") Colour LCD Screen		
Mobile and Cloud Printing			
Epson Connect	Epson Smart Panel, Epson Email Print, Remote Print Driver		
Driverless Solutions	Apple AirPrint, Mopria Print Service, Chrome OS		
Supported Operating Systems			
Vindows	Windows 7 / 8 / 8.1 / 10 / 11, Windows Server 2008 / 2012 / 2016 / 2019 / 2022 / 2025		
Mac	Mac OS X 10.9.5 or later, macOS 11 or later		
Printer Software			
Software Solutions Compatibility	Epson Photo+, Epson ScanSmart, Epson Device Admin, Epson Remote Services		
lectrical Specifications			
ated Voltage	AC 220-240 V		
ated Frequency	50 - 60 Hz		
ower Consumption			
Operating	13 W		
Standby	6.2 W		
Sleep	0.6 W		
Power Off	0.1 W		
loise Level	Sec. 11		
PC Printing / Premium Glossy Photo Paper	Cound Dower (Plants / Onlaws) 5.0 / 5.4 P/A)		
Best Photo	Sound Power (Black / Colour) 5.3 / 5.4 B(A),		
PC Printing / Plain Paper Default*4	Sound Pressure (Black / Colour) 40 / 40 dB(A)		
Cany / Flair Fapor Dolaum	Sound Power (Black / Colour) 6.6 / 5.8 B(A),		
	Sound Pressure (Black / Colour) 53 / 45 dB(A)		
pson Consumable	-	er Code	
Black Ink Bottle	8,500 pages 001	C13T03Y198	
Cyan Ink Bottle		C13T03Y298	
Jagenta Ink Bottle	6 500 (Composite Vield) 001	C13T03V308	

Dimensions & Weight

L4360 Weight: 5.2 kg



\*1 Print speed (Pages Per Minute) is calculated when printed on A4 plain paper in the fastest mode, 10 x 15 cm photo print speed when printed on Epson Premium Glossy Photo Paper. Print speed may vary depending on system configuration, print mode, document complexity, software, type of paper used and connectivity. Print speed does not include processing time on host computer.



- \*2 When printed on Epson Premium Glossy Photo Paper
- \*3 Borderless printing is supported up to A4, otherwise 3mm top, left, right, bottom.
- \*4 Default mode in accordance with ISO7779 for MFPs.
- \*5 Quoted yields are extrapolated based on Epson original methodology from the print simulation of Test Patterns provided in ISO/IEC 24712. Quoted yields are NOT based on ISO/IEC 24711. Quoted yields may vary depending on the images that you are printing, the paper type that you are using, the frequency of your prints and environmental conditions such as temperature. During the initial printer setup, a certain amount of ink is used to fill the print head's nozzles, therefore the yield of the initial bundled set can be lower.

© 2025 Epson India Pvt. Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited. EPSON is registered trademark of Seiko Epson Corporation. All other products names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. Print samples shown are simulations only. Specifications and product availability are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct as of April 2025.

### **EPSON INDIA PVT. LTD.**

Magenta Ink Bottle

Yellow Ink Bottle

Maintenance Box

11th Floor, Godrej Centre, Hebbal, Survey No. 26, Bellary Road, Sahakar Nagar, Byatarayanapura, Bangalore 560 092, Karnataka. Tel: 080 6939 5000. Fax: 080 6939 5005

### **Regional Offices:**

Ahmedabad 4037 0075, Chennai 4905 5177, Coimbatore 98942 19200, Ernakulam 4012 315, Hyderabad 4857 0032, Jaipur 4923 119, Kolkata 4603 4714/15/29/30, Mumbai 3079 8200, New Delhi 4107 3101, 4752 2414, Pune 2998 0641

001



6,500 (Composite Yield)

C13T03Y398

C13T03Y498

C13T04D198